Bundling and Securing

Clamps

Inline Ratchet P-Clamp



Inline Ratchet P-Clamps take our popular RPC product family to new places and applications. The Inline RPCs feature several of our industryleading, built-in attachments. That means, instead of fastening them with a screw or bolt, installers can utilize a choice of round or oval fir trees as well as adhesive mounts. No tools or additional hardware are needed for securing to a hole or panel.

The robust design delivers 100 lb tensile strength and, combined with impact-resistant PA66 material, makes them ideal for heavy duty applications both indoors and out. The fir trees exhibit low insertion force and high extraction resistance.

The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface.

Features and Benefits

- Clamp and mount combination means no extra hardware is needed.
- Mount is directly below clamp as opposed to offset, providing a smaller footprint.
- One-piece ratchet closure is easier to open than standard metal clamps, for time-saving, toolless, one-handed installation during pre- or final assembly.
- Plastic construction is safe on bundles, won't chafe or crush.
- Clamp saddle provides additional routing option using a cable tie, eliminating the need to drill or add complex routing parts.
- PA66HIRHSUV material stands up to extreme temperatures, chemicals, salt spray and constant UV light exposure.

Markets

- Heavy equipment
- Truck
- Automotive
- Machine builders

- Rail
- Renewables
- Utility

HellermannTyton

Bundling and Securing Clamps

Inline Ratchet P-Clamp

PART NO.	ТҮРЕ	Min. Bundle Diameter in. (mm)	Max. Bundle Diameter in. (mm)	Mounting Hole Dia. in. (mm)	Panel Thickness in. (mm)	Width (W) in. (mm)	Adhesive	Pkg. Qty.
Adhesive	Y	1						
156-02722	IRCAMB5A	0.2 (6.1)	0.5 (13.7)	-		1.4 (34.9)	Acrylic	25
156-02723	IRCBMB5A	0.5 (12.7)	0.8 (19.6)	-		1.4 (34.9)	Acrylic	25
156-02724	IRCCMB5A	0.8 (19.3)	1.4 (36.0)	-		1.4 (34.9)	Acrylic	25
156-02725	IRCDMB5A	1.4 (36.0)	2.0 (50.8)	-		1.4 (34.9)	Acrylic	25
Fir Tree for oval holes								
156-02718	IRCAFT9X17	0.2 (6.1)	0.5 (13.7)	0.35 x 0.67 (9.0 x 17.0)	0.02 - 0.27 (0.6 - 6.8)	1.4 (34.9)	-	25
156-02710	IRCAFTOVAL	0.2 (6.1)	0.5 (13.7)	0.28 x 0.47 (7.0 x 12.0)	0.02 - 0.27 (0.6 - 6.8)	1.4 (34.9)	-	25
156-02719	IRCBFT9X17	0.5 (12.7)	0.8 (19.6)	0.35 x 0.67 (9.0 x 17.0)	0.02 - 0.27 (0.6 - 6.8)	1.4 (34.9)	-	25
156-02711	IRCBFTOVAL	0.5 (12.7)	0.8 (19.6)	0.28 x 0.47 (7.0 x 12.0)	0.02 - 0.27 (0.6 - 6.8)	1.4 (34.9)	-	25
156-02720	IRCCFT9X17	0.8 (19.3)	1.4 (36.0)	0.35 x 0.67 (9.0 x 17.0)	0.02 - 0.27 (0.6 - 6.8)	1.4 (34.9)	-	25
156-02712	IRCCFTOVAL	0.8 (19.3)	1.4 (36.0)	0.28 x 0.47 (7.0 x 12.0)	0.02 - 0.27 (0.6 - 6.8)	1.4 (34.9)	-	25
156-02721	IRCDFT9X17	1.4 (36.0)	2.0 (50.8)	0.35 x 0.67 (9.0 x 17.0)	0.02 - 0.27 (0.6 - 6.8)	1.4 (34.9)	-	25
156-02713	IRCDFTOVAL	1.4 (36.0)	2.0 (50.8)	0.28 x 0.47 (7.0 x 12.0)	0.02 - 0.27 (0.6 - 6.8)	1.4 (34.9)	-	25
Fir tree for round holes								
156-02706	IRCAFT6.5LG	0.2 (6.1)	0.5 (13.7)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	1.4 (34.9)	-	25
156-02714	IRCAFT9LG	0.2 (6.1)	0.5 (13.7)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	1.4 (34.9)	-	25
156-02707	IRCBFT6.5LG	0.5 (12.7)	0.8 (19.6)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	1.4 (34.9)	-	25
156-02715	IRCBFT9LG	0.5 (12.7)	0.8 (19.6)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	1.4 (34.9)	-	25
156-02708	IRCCFT6.5LG	0.8 (19.3)	1.4 (36.0)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	1.4 (34.9)	-	25
156-02716	IRCCFT9LG	0.8 (19.3)	1.4 (36.0)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	1.4 (34.9)	-	25
156-02709	IRCDFT6.5LG	1.4 (36.0)	2.0 (50.8)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	1.4 (34.9)	-	25
156-02717	IRCDFT9LG	1.4 (36.0)	2.0 (50.8)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	1.4 (34.9)	-	25

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes. For more information, go to www.Hellermann.Tyton.com.

HellermannTyton